



Produtos



Contato



Imprimir

Correias Transportadoras

<< voltar



Tipo	EP140/PN1200		EP220/PN220					EP320/PN3000				EP420/PN4000				EP500/PN5000			
Nº de Lonas	2	3	2	3	4	5	6	2	3	4	5	3	4	5	6	4	5	6	
Tensão Admissível (kgf/cm)	25	37.5	44	66	88	110	132	66	99	132	165	132	176	220	264	200	250	300	
Peso da Carcaça (kg/m)	2.30	3.45	3.90	6.00	6.30	7.90	9.5	3.90	5.85	7.80	9.75	6.5	8.6	10.80	13.00	10.00	12.50	15.00	
Espessura da Carcaça	2.2	3.3	3.9	5.2	5.4	6.6	8.0	3.4	5.1	6.7	8.3	6.2	8.3	10.3	12.3	9.2	11.5	13.8	
Largura Máxima (pol)	20°	12	20	18	24	30	30	42	20	30	36	42	30	36	42	48	36	42	48
	35°	14	20	18	24	30	36	48	24	30	36	42	30	36	42	48	42	48	48
	45°	18	20	24	30	36	42	54	32	36	42	48	36	42	48	54	42	48	54
Largura Máxima ar=20°	0 a 800	40	48	54	72	84	90	94	66	84	94	94	88	88	94	94	94	94	94
	800 a 1600	32	42	48	72	72	88	88	60	72	84	88	84	84	88	94	88	94	94
	1600 a 2400	32	36	42	60	72	84	84	60	72	84	84	72	84	84	88	84	88	94
Largura Máxima ar=35°	0 a 800	36	42	48	66	72	84	88	60	72	88	88	84	88	88	94	94	94	94
	800 a 1600	30	36	42	60	66	72	84	54	66	72	84	72	84	84	94	88	94	94
	1600 a 2400	24	32	36	54	66	66	72	54	60	72	84	66	84	84	88	84	88	88
Largura Máxima ar=40°	0 a 800	32	36	48	55	72	84	88	48	66	84	88	84	84	88	88	88	94	94
	800 a 1600	26	32	42	48	66	72	84	48	60	72	84	72	84	84	84	84	88	94
	1600 a 2400	20	26	36	42	60	66	72	42	54	60	72	60	72	84	84	84	84	88
2400 a 3200	-	24	32	42	54	60	66	36	48	60	60	54	72	84	84	72	72	84	

Tipo	AB, EA, AT, ATS, OAN, AC, SAS, EAR, TG, TGS																		
Diâmetro Mínimo dos Tambores	100 a 80	400	450	450	500	600	750	900	500	600	750	900	7750	900	1050	1200	900	1050	1200
	80 a 60	350	400	400	450	500	600	750	450	500	600	750	600	750	900	1050	750	900	1050
	60 a 40	300	350	350	400	450	500	600	400	450	500	600	500	600	750	900	600	750	900
	40 a 0	250	300	300	350	400	450	500	350	400	450	500	450	500	600	750	500	600	750